

SHAFTS -BOTH SIDES MALE SCREW HOLLOW TYPE-

シャフト 両端おねじパイプタイプ



Technical drawing and specifications for SPJM, PSPJM, RSPJM shafts. Includes material (SUJ2), hardness (58HRC), and surface treatment (black chrome plating). Dimensions include diameter (D), length (L), and thread specifications (M, N, P, Q).

カタログ規格外品はこちら P.137 CADデータフォルダ名: 01_Shfts

Table with columns: Type, Dg6, L, F・T, B・S, P・Q 選択, d, (Y) Max., R, C. Lists specifications for SPJM, PSPJM, RSPJM shafts.

D=P・D=Qの場合、B(S)寸法はF=B(T=S)でご指定ください。但し寸法・F寸法・T寸法を優先して製作しますので製品のB(S)寸法はF(T)・(Pitch×2)となります。

B=0・S=0の場合、ねじ加工を行います。B・S≥Pitch×3が必要です。

Order form for RSPJM shafts. Includes fields for quantity, price, and delivery date.

Order form for SPJM shafts. Includes fields for quantity, price, and delivery date.

Price table for RSPJM shafts. Columns: 数量区分, 標準対応, 個別対応.

Price table for SPJM shafts. Columns: 数量区分, 標準対応, 個別対応.

Table for low-temperature black chrome plating additional charges. Columns: D, 最短L, L51~100, L101~150, L151~200, L201~300, L301~400, L401~500.

Table for low-temperature black chrome plating additional charges. Columns: D, 最短L, L51~100, L101~150, L151~200, L201~300, L301~400, L401~500.

低温黒色クロムメッキ品は、下記表面処理無し基準単価に上記低温黒色クロムメッキ追加価格を加算してください。

追加加工による硬度低下の可能性がります。P.148参照

Main specification table for SPJM, PSPJM, RSPJM shafts. Columns: 型式, Type, D, 最短L, L51~100, L101~150, L151~200, L201~300, L301~400, L401~500, L501~600, L601~800, L801~1000, L1001~1200, L1201~1496.

SHAFTS -ONE SIDE MALE SCREW THE OTHER SIDE FEMALE SCREW HOLLOW TYPE-

シャフト 片端おねじ片端めねじパイプタイプ



Technical drawing and specifications for SPJD, PSPJD, RSPJD shafts. Includes material (SUJ2), hardness (58HRC), and surface treatment (black chrome plating). Dimensions include diameter (D), length (L), and thread specifications (M, N, P, Q).

カタログ規格外品はこちら P.137 CADデータフォルダ名: 01_Shfts

Table with columns: Type, Dg6, L, F, B, P 選択, N(並目) 選択, d, (Y) Max., R, C. Lists specifications for SPJD, PSPJD, RSPJD shafts.

D=Pの場合、B寸法はF=Bでご指定ください。但し寸法・F寸法を優先して製作しますので、製品のB寸法はF・(Pitch×2)となります。

B=0を指定した場合、ねじ加工を行いません。全長Lは、N×3≦Lが必要。

Order form for RSPJD shafts. Includes fields for quantity, price, and delivery date.

Order form for SPJD shafts. Includes fields for quantity, price, and delivery date.

Price table for RSPJD shafts. Columns: 数量区分, 標準対応, 個別対応.

Price table for SPJD shafts. Columns: 数量区分, 標準対応, 個別対応.

Table for low-temperature black chrome plating additional charges. Columns: D, 最短L, L51~100, L101~150, L151~200, L201~300, L301~400, L401~500.

Table for low-temperature black chrome plating additional charges. Columns: D, 最短L, L51~100, L101~150, L151~200, L201~300, L301~400, L401~500.

低温黒色クロムメッキ品は、下記表面処理無し基準単価に上記低温黒色クロムメッキ追加価格を加算してください。

追加加工による硬度低下の可能性がります。P.148参照

Main specification table for SPJD, PSPJD, RSPJD shafts. Columns: 型式, Type, D, 最短L, L51~100, L101~150, L151~200, L201~300, L301~400, L401~500, L501~600, L601~800, L801~1000, L1001~1200, L1201~1496.