

DOWEL PINS ノックピン

小物部品



RoHS10

MS (ストレートタイプ)

材質 SUJ2
硬度 58HRC~

ℓ1	型式		L													
	Type	D														
0.4	MS	1	6	8	10											
0.6		1.5	6	8	10											
1.0		2	6	8	10	15	20									
		2.5	6	8	10	15	20	25	30							
1.5		3	6	8	10	15	20	25	30	35	40					
		4	8	10	15	20	25	30	35	40	45	50				
2.0		5	8	10	15	20	25	30	35	40	45	50				
2.5		6	8	10	15	20	25	30	35	40	45	50	55	60		
3.0		8	10	15	20	25	30	35	40	45	50	55	60	65	70	80
3.5		10	15	20	25	30	35	40	45	50	55	60	65	70	80	
		12	20	25	30	35	40	45	50	55	60	70	80			
		13	30	40	50	60	70	80								

ℓ1寸法は参考値です。

MSV (高精度タイプ)

材質 SUJ2
硬度 58HRC~

ℓ1	ℓ2	型式		L											
		Type	D												
1.0	0.2	MSV	2	6	8	10									
			3	8	10	15	20	25	30						
4	10		15	20	25	30									
5	10		15	20	25	30									
6	10		15	20	25	30									
8	20		30	40											
10	30		40	50	60										
1.5	0.5		2	6	8	10									
3			8	10	15	20	25	30							
2.0	4		10	15	20	25	30								
2.5	5	10	15	20	25	30									
3.0	6	10	15	20	25	30									
	8	20	30	40											
	10	30	40	50	60										

ℓ1・ℓ2寸法は参考値です。
高精度タイプノックピンは恒温室にて測定しています。

MSTP (タップ付精級タイプ)

材質 SUJ2
硬度 58HRC~

ℓ1	M×P	ℓ	D	型式		L									
				Type	D										
1.5	3×0.5	*6	+0.010 +0.005	MSTP	5	10	15	20	25	30					
					6	10	15	20	25	30	35	40	50		
8	15	20			25	30	35	40	45	50	60	70	80		
10	15	20			25	30	35	40	45	50	60	70	80		
12	20	30			40	50	60	70	80						
13	40	50			60	70	80								
16	40	50			60	70									
2.0	4×0.7	*8			5	10	15	20	25	30					
6					10	15	20	25	30	35	40	50			
2.5	6×1.0	10			8	15	20	25	30	35	40	45	50	60	70
			10	15	20	25	30	35	40	45	50	60	70	80	
3.0	8×1.25	15	12	20	30	40	50	60	70	80					
			16	40	50	60	70								

ℓ1寸法は参考値です。
*D=5の場合、ℓ=6は参考値です。 *D=6、L=10の場合のみℓ=6

MST (タップ付p6タイプ)

材質 SUJ2
硬度 45~50HRC

ℓ1	ℓ2	M×P	ℓ	Dp6	型式		L									
					Type	D										
1.5	0.5	3×0.5	*6	+0.020 +0.012	MST	5	10	15	20	25	30					
						6	10	15	20	25	30	35	40	50		
8	15	20	25			30	35	40	45	50	60	70	80			
10	15	20	25			30	35	40	45	50	60	70	80			
12	20	30	40			50	60	70	80							
13	40	50	60			70	80									
16	40	50	60			70	80									
2.0	4×0.7	*8	5			10	15	20	25	30						
6			10			15	20	25	30	35	40	50				
2.5	5×0.8	*8	8			15	20	25	30	35	40	45	50	60	70	80
			10	15	20	25	30	35	40	45	50	60	70	80		
3.0	6×1.0	10	12	20	30	40	50	60	70	80						
			13	40	50	60	70	80								
1.0	8×1.25	15	16	40	50	60	70	80								
			20	50	60	70	80									
2.5	6×1.0	10	12	20	30	40	50	60	70	80						
			13	40	50	60	70	80								
3.0	10×1.5	18	20	50	60	70	80									
			25	60	70	80										

ℓ1・ℓ2寸法は参考値です。
*D=5の場合、ℓ=6は参考値です。 *D=6、L=10の場合のみℓ=6

MSTM (タップ付m6タイプ)

材質 SUJ2
硬度 45~50HRC

ℓ1	ℓ2	M×P	ℓ	Dm6	型式		L									
					Type	D										
1.5	0.3	3×0.5	*6	+0.012 +0.004	MSTM	5	10	15	20	25	30					
						6	10	15	20	25	30	35	40	50		
8	15	20	25			30	35	40	45	50	60	70	80			
10	15	20	25			30	35	40	45	50	60	70	80			
12	20	30	40			50	60	70	80							
13	40	50	60			70	80									
16	40	50	60			70	80									
2.0	0.5	4×0.7	*8			5	10	15	20	25	30					
6						10	15	20	25	30	35	40	45	50	60	70
2.5	1.0	5×0.8	10			8	15	20	25	30	35	40	45	50	60	70
				10	15	20	25	30	35	40	45	50	60	70	80	
3.0	1.5	8×1.25	15	12	20	30	40	50	60	70	80					
				18	40	50	60	70	80							

ℓ1・ℓ2寸法は参考値です。
*D=5の場合、ℓ=6は参考値です。 *D=6、L=10の場合のみℓ=6

MTT (タップ付テーパタイプ)

材質 SK4
硬度 45~50HRC

M×P	ℓ	型式		L			
		Type	D				
5×0.8	9	MTT	8	30	40		
6×1.0	10		10	40	50		
			12	40	50		
8×1.25	14		13	50	60		
10×1.5	16	16	60	70			

MSSH (ストレートh7タイプ)

材質 SUJ2
硬度 58HRC~

ℓ1	Dh7	型式		L					
		Type	D						
1.0	0 -0.010	MSSH	2	6	8	10	15		
			3	8	10	15	20		
1.5	0 -0.012		4	10	15	20			

ℓ1寸法は参考値です。

MSTH (タップ付h7タイプ)

材質 SUJ2
硬度 45~50HRC

ℓ1	ℓ2	M×P	ℓ	Dh7	型式		L									
					Type	D										
1.5	0.3	3×0.5	*6	0 -0.012	MSTH	5	10	15	20	25	30					
						6	10	15	20	25	30	35	40	50		
8	15	20	25			30	35	40	45	50	60	70	80			
10	15	20	25			30	35	40	45	50	60	70	80	100	120	
12	20	30	40			50	60	70	80	100	120					
13	40	50	60			70	80	100	120							
16	40	50	60			70	80	100	120	150						
2.0	0.5	4×0.7	*8			5	10	15	20	25	30					
6						10	15	20	25	30	35	40	45	50	60	70
2.5	1.0	5×0.8	10			8	15	20	25	30	35	40	45	50	60	70
				10	15	20	25	30	35	40	45	50	60	70	80	100
3.0	1.5	8×1.25	15	12	20	30	40	50	60	70	80	100	120	150		
				18	40	50	60	70	80	100	120	150				

ℓ1・ℓ2寸法は参考値です。
*D=5の場合、ℓ=6は参考値です。 *D=6、L=10の場合のみℓ=6

Order 注文例
型式 MS2 - L 10

Delivery 出荷日
在庫品

エアベント深さ 0.15
バレル研磨仕上げのため、参考値です。
全D寸に共通
対象品目: MSTP, MST, MSTM, MSTH